

XB Subwoofers

Power Subwoofers featuring BassTrac®

Our new XB Subwoofers offer a clean, contemporary style that is visually more compatible with modern interiors. New style elements include a lower, slightly wider footprint, gently rounded corners, metal grilles, and flush-mounted volume controls on top of the XB8, XB6, and XB4. All are available in black ash. All four are front-firing, front-ported, and very easy to install.

The XB subwoofers are equipped with Deep Channel™ woofers that deliver extended excursion with increased bass response, and Boston's exclusive BassTrac circuitry, designed to eliminate distortion. A 24dB/octave lowpass filter on each subwoofer prevents it from being easily localized by ear, increasing placement flexibility. Also provided are variable crossovers, phase controls, rear-panel line and speaker level inputs, and a crossover bypass function for Home Theater components that perform their own bass management.

The XB8 and XB6 powered subwoofers feature large 12-inch Deep Channel woofers, BassTrac circuitry, and powerful amplifiers in vented enclosures. The XB8 has a FTC-rated 300-watt amplifier and the XB6 has a 200-watt amplifier. The XB8 and XB6 have a frequency response (+/-3dB) of 26Hz-150Hz and 29Hz-150Hz respectively. The volume control is mounted on top of the cabinet, flush with the surface, so the top remains perfectly flat.



The XB4 Powered Subwoofer features a 10-inch Deep Channel woofer, BassTrac circuitry, an FTC-rated 100-watt amplifier in a vented enclosure, and a frequency response (+/-3dB) of 38Hz-180Hz. As in the XB8 and XB6, the volume control is conveniently mounted flush with the top of the cabinet.

The XB2 Powered Subwoofer features an 8-inch Deep Channel woofer, BassTrac circuitry, an FTC-rated 50-watt amplifier in a vented enclosure, and a frequency response (+/-3dB) of 45Hz-200Hz.

All XB Subwoofers deliver The Boston Sound; the sound the artist intended. Pure, natural, true-to-the-original performance®.



XB8



XB6



XB4



XB2

	XB8	XB6	XB4	XB2
Frequency Response (± 3dB)	26Hz-150Hz	29Hz-150Hz	38Hz-180Hz	45Hz-200Hz
Subwoofer Amplifier Power	900 watts dynamic power output, FTC Rated Power: 300 watts @ 50Hz into 4 ohms at less than 1% THD+N	625 watts dynamic power output, FTC Rated Power: 200 watts @ 50Hz into 4 ohms at less than 1% THD+N	400 watts dynamic power output, FTC Rated Power: 85 watts @ 50Hz into 4 ohms at less than 1% THD+N	210 watts dynamic power output, FTC Rated Power: 50 watts @ 50Hz into 4 ohms at less than 1% THD+N
Subwoofer Crossover	50Hz-150Hz, 24dB/octave lowpass	50Hz-150Hz, 24dB/octave lowpass	75Hz-150Hz, 24dB/octave lowpass	75Hz-200Hz, 24dB/octave lowpass
LFE Input	Yes	Yes	Yes	
Crossover Bypass	Yes	Yes	Yes	Yes
Bass Unit	12" (305mm) DCD	12" (305mm) DCD	10" (254mm) DCD	8" (203mm) DCD
Enclosure Type	Ported, Front Firing	Ported, Front Firing	Ported, Front Firing	Ported, Front Firing
Dimensions (HxWxD) (with feet and rear connections)	13 ³ / ₄ x 15 ¹ / ₂ x 16 ⁷ / ₁₆ " (350 x 395 x 417mm)	13 ³ / ₄ x 15 ¹ / ₂ x 13 ¹³ / ₁₆ " (350 x 395 x 354mm)	12 ³ / ₁₆ x 14 ⁷ / ₁₆ x 13 ⁷ / ₁₆ " (310 x 360 x 341mm)	11 ¹¹ / ₁₆ x 14 ⁵ / ₈ x 13 ⁷ / ₁₆ " (297 x 371 x 336mm)
Product Weight	31 lbs (14.1kg)	28 lbs (12.7kg)	26 lbs (11.8kg)	21 lbs (9.52kg)

Covered by patents issued and/or pending. Specifications subject to change without notice.

© 2006. All rights reserved. Deep Channel and Your Sound Solution are trademarks and BassTrac, Boston, Boston Acoustics, the Boston logo and true-to-the-original performance are registered trademarks of Boston Acoustics, Inc.